

Darkroom Safelight Filters

Kodak Safelight Filters

Suitable for fitting to the above safelights. Other sizes and types available on request.

- OA** Light yellow for slow, blue sensitive contact materials
- 1** Red for slow orthochromatic and fast, blue sensitive materials
- 1A** Light red for Kodalith orthochromatic materials

- | | |
|--|--|
| L077-F01 type OA, 140mm (5.5") diam. | L077-F06 type 1A, 254 x 305mm (10" x 12") |
| L077-F02 type OA, 201 x 254mm (8"x10") | L077-F07 type 1, 140mm (5.5mm) diam. |
| L077-F03 type OA, 254 x 254mm (10"x12") | L077-F08 type 1, 201x 254mm(8"x10") |
| L077-F04 type 1A, 140mm (5.5") diam. | L077-F09 type 1, 254 x 305mm (10"x12") |
| L077-F05 type 1A, 201 x 254mm (8"x10") | |



Film Drying Cabinets

The Marrutt range of film drying cabinets are strongly constructed from zinc and epoxy coated steel making them resistant to scratching and corrosion. The internal construction is of stainless steel and the units are fitted with a *TURBOFLOW* air system that is filtered to a 96% efficiency. They are supplied complete with no hidden extras. The model 36/35 will accept 12 full length 35mm films completely extended and will also accept the 220 film length of 1625mm. A certain amount of cut film can also be accommodated. For larger amounts of cut film the model 80 is recommended.

Dimensions:

Model 36/35 203cm High x 36cm Wide x 36cm Deep

Model 80 175cm High x 63cm Wide x 57cm Deep

D124 Film drying cabinet Model 36/35 240v

D124/1 Film drying cabinet Model 36/35 110V

D125 Film drying cabinet Model 80 240v

D125/1 Film drying cabinet Model 80 110v

Important Note:

The drying cabinets contain high efficiency **filter elements** which must be checked and replaced if necessary every 6 months.

D124/F Filter for model 36/35 cabinet

D125/F Filter for model 80 cabinet

