

Langford Sonomatic Ultrasonic Cleaners & Accessories



Models T80, 175



Models 375, 475, 575

Now only available with heaters and timers

All British high quality units with outer case and cleaner tank manufactured from rigid stainless steel. Power source uses double halfwave high frequency generators resulting in extremely efficient cleaning.

These cleaners are maintenance free, CE marked and there are models available with temperature control of the cleaning fluid (set at either 60°C or variable from 20°C to 80°C). The ultrasonic cycle time is fixed at either 15 minutes or (optionally) adjustable from 0 - 60 minutes.

Accessories: Lids (ABS) and Baskets (stainless steel).

Sonomatic Ultrasonic Cleaners

Catalogue Number		C075	C135	C152	C152/H	C152/TT	C136	C136/H	C136/TT	C137	C137/H	C137/TT
Model Type		T80	T175	375			475			575		
Overall Dimensions (mm)	Height	175	175	310			310			370		
	Width	110	165	162			162			175		
	Length	135	175	200			250			250		
Weight (Kgs)		1.4	2.4	2.7			3.5			4.1		
Internal Dimensions (mm)	Height	151	151	240			240			300		
	Width	83	137	135			135			150		
	Length	65	100	100			150			150		
Tank Volumes (litres)		0.6	1.6	2.3			3.6			4.9		
High Frequency Peak Power (watts)		80	100	150			300			300		
High Frequency Power Output (watts)		-	-	75			150			150		
Frequency approx. (kHz)		40	40	40			40			40		
Power Consumption (watts)		80	90	100	290	290	200	410	410	200	460	460
Fuses (all types) (A)		1,0M	1,0M	← 2,0M →			← 3,15M →			← 3,15M →		
Heating Capacity (watts)		n/a	n/a	n/a	200	200	n/a	300	300	n/a	300	300
Temperature Control of Tank Fluid												
Approx. 60° thermostatic control		n/a	n/a	n/a	✓	n/a	✓	n/a	n/a	n/a	✓	n/a
Thermostatic control 20-80°C		n/a	n/a	n/a	n/a	✓	n/a	✓	n/a	n/a	n/a	✓
Timer Control, Ultrasonics												
Preset fixed cycle time, max. 15 mins		✓	✓	✓	✓	-	✓	✓	-	-	-	✓
Adjustable from 0 - 60 mins		-	-	-	-	✓	-	-	✓	-	-	✓

Larger models available on request